



Color: Green With Cream Helix.

Temperature range: - 10°C + 60°C / + 14°F + 140°F.

Features: PVC hose reinforced with an ANTI- SHOCK RIGID PVC spiral. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, abrasion, atmospherical agents and most chemicals.

Applications: Excellent for suction in general, particularly suitable to be used on slurry machines.

Extensively used for suction & Discharge of public utilities, Drainage, Ships, Silos & Irrigation plants.

TECHNICAL DATA

PART NUMBER	INSIDE Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Working Pressure	Burst Pressure	Vacuum	Bending Radius	Roll Length	Volume
	mm	mm	mm	g/m	Bar	Bar	m H2O	mm	m	m³
01 020. 0 000	20.00	3.10	3.50	300	7.00	21.00	10.00	100	50	0.070
01 025. 0 000	25.00	3.30	3.70	390	6.00	18.00	10.00	125	50	0.094
01 032. 0 000	31.80	3.90	4.30	580	6.00	18.00	10.00	160	50	0.142
01 038. 0 000	38.10	3.80	4.40	670	5.00	15.00	10.00	190	50	0.190
01 050. 0 000	50.00	4.20	4.80	960	4.00	12.00	10.00	250	50	0.310
01 052. 0 000	50.80	4.20	4.80	970	4.00	12.00	10.00	250	50	0.314
01 063. 0 000	63.50	4.70	5.30	1350	4.00	12.00	9.00	315	50	0.501
01 076. 0 000	76.20	4.90	5.60	1630	3.00	9.00	9.00	380	50	0.646
01 080. 0 000	80.00	5.00	5.90	1770	3.00	9.00	9.00	400	50	0.720
01 100. 0 000	100.00	5.90	6.90	2590	3.00	9.00	8.50	500	30	0.768
01 102. 0 000	102.00	5.90	6.90	2640	3.00	9.00	8.50	500	30	0.782
01 127. 0 000	127.00	6.20	7.30	3450	2.50	7.50	8.00	630	30	1.228
01 150. 0 000	151.50	6.70	7.90	4420	2.00	6.00	7.00	750	20	1.312
01 152. 0 000	152.40	6.70	7.90	4410	2.00	6.00	7.00	750	20	1.319

Authorized Distributor:
GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service

✉ E-mail: sales@geo-mac.com
www.geo-mac.com

📍 Shop No. 0, Building 270, Road / Street 336
Block 312, MANAMA / ALGUFUL
Kingdom of Bahrain

☎ Phone Number: +973 17769636