

## BULK CEMENT SUCTION HOSE

150 PSI



## TECHNOFLEX - DRY/WET BULK MATERIAL SUCTION HOSE 150 PSI - W. P.

MADE IN ITALY

Abrasion resistant tube and cover fabricated with highest quality elastomer compounds for maximum performance. Used in the transfer of dry/wet materials & slurries and ideal for dry/wet cement, pebble, lime brine, barite and other abrasive media.

- Safety Factor:
  - o 4:1
- Tube/Cover:
  - Black NR/SBR rubber blend.
- Temperature:
  - -20°F to + 180°F (-30°C 10 + 80°C).
- Reinforcement:
  - Multiple textile plies with antistatic wire helix.
- Branding:
  - TECHNOFLEX ITALY BULK CEMENT SUCTION HOSE 150 PSI W. P.

| I.D.    |       | O.D. | Standard Length |    | Working Pressure |     | Burst Pressure |     | Approx.<br>Weight |
|---------|-------|------|-----------------|----|------------------|-----|----------------|-----|-------------------|
| in      | mm    | mm   | ft              | m  | psi              | bar | psi            | bar | kg/m              |
| 2       | 50.8  | 70   | 200             | 60 | 150              | 10  | 450            | 30  | 3.33              |
| 2 - 1/2 | 63    | 89   | 200             | 60 | 150              | 10  | 450            | 30  | 3.95              |
| 3       | 76.2  | 96   | 200             | 60 | 150              | 10  | 450            | 30  | 5.00              |
| 4       | 101.6 | 124  | 200             | 60 | 150              | 10  | 450            | 30  | 6.55              |
| 5       | 127   | 153  | 200             | 60 | 150              | 10  | 450            | 30  | 8.28              |
| 6       | 152   | 170  | 200             | 60 | 150              | 10  | 450            | 30  | 9.83              |

Authorized Distributor:
GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service