

TECHNOFLEX LAY FLAT HOSE

Description:

Smooth and seamless inner surface, particularly resistant to elongation, smooth cover. Very high adhesion between inner and outer layers. Highly resistant to abrasion and ageing, high tenacity polyester yarn reinforced inner black coating.

Applications:

Equipment Rental, Construction, Agricultural, General Open End Water Discharge.

NOMINAL SPECIFICATIONS

SERIES NO.	SIZE (IN)	HOSE ID (IN)	APPROXIMATE WALL THICKNESS (IN)	WORKING PRESSURE (BAR)	COIL LENGTH (MTR)	APPROX. WEIGHT (LBS/COIL)
TFFH200	2	2.087	0.055	4	100	49.0
TFFH300	3	3.071	0.059	4	100	90.0
TFFH400	4	4.094	0.059	4	100	131.0
TFFH600	6	6.102	0.071	4	100	209.0
TFFH800	8	8.169	0.083	4	100	312.0
TFFH1000	10	10.197	0.091	4	100	409.0
TFFH1200	12	12.203	0.098	4	100	517.0

**TEMPERATURE
RANGE:**
-10°C +80°C

Note:

Layflat Hose will come without fittings.

When using Layflats with fittings it is essential that a sleeve of layflat is used as a reinforcement under the fitting/clamp.

MADE IN KOREA