

TECHNOFLEX LAY FLAT HOSE HEAVY DUTY

Description:

Heavy Duty smooth and seamless inner surface, particularly resistant to elongation. Constructed with high grade strength polyester yarn reinforcement. Lightweight and compact for economical storage. Highly resistant to abrasion and ageing, chemical and UV resistant. Excellent mobility and high pressure resistance.

Applications:

Mining, Irrigation, Construction, Industrial, Quarry, High pressure sprinkling & dewatering, Light gravel or mud discharge.



NOMINAL SPECIFICATIONS

SERIES NO.	SIZE (IN)	HOSE ID (IN)	APPROXIMATE WALL THICKNESS (IN)	WORKING PRESSURE (AT 20°C) (BAR)	BURST PRESSURE (AT 20°C) (BAR)	COIL LENGTH (MTR)	APPROX. WEIGHT (KGS/COIL)
TFRFH200	1 ½"	1.578	0.074	10.5	30	100	30.0
TFRFH300	2"	2.047	0.078	10.5	30	100	42.0
TFRFH400	2 ½"	2.559	0.086	10.5	30	100	56.0
TFRFH600	3"	3.031	0.086	10.5	30	100	70.0
TFRFH800	4"	4.094	0.102	10.5	30	100	110.0
TFRFH1000	6"	6.141	0.116	10.5	30	100	168.0
TFRFH1200	8"	8.149	0.120	10.5	30	100	240.0

**TEMPERATURE
RANGE:**
-6°C +80°C

Note:

Layflat Hose will come without fittings.

When using Layflats with fittings it is essential that a sleeve of layflat is used as a reinforcement under the fitting/clamp.

MADE IN KOREA