

PETROLEUM OIL HOSE

300 PSI / 20 BAR

MADE IN ITALY



TechnoFlex Petroleum Oil Hose - 300 PSI / 20 BAR

A high-performance suction and discharge hose specifically designed for the transfer of petroleum products, including gasoline, oil, and those with aromatic content up to 50%. Built to excel in demanding environments such as oil field loading and unloading operations, this premium hose features a multi-layer construction that ensures exceptional strength, flexibility, and durability. Engineered for reliability in tough conditions, it delivers efficient and secure transfer of petroleum products with uncompromising performance.

- Temperature range:
 - -30°C to +70°C
- **Reinforcement:**
 - High multiple textile piles with dual helix steel wire with ANTI-STATIC.
- Tube:
 - Black high grade of oil resistant (NBR).
- - o Abrasion, oil, weather & ozone resistant (CR).
- Standard length:
 - o 30m /60m
- Safety Factor:
 - 0 4:1

HOSE I.D.		HOSE O.D.		STANDARD LENGTH		WORKING PRESSURE		BURST PRESSUER		MINIMUM BEND RADIUS		WEIGHT
INCH	MM	INCH	MM	FEET	METERS	PSI	BAR	PSI	BAR	INCH	ММ	GR/M
1 1/2	38.1	1.953	49.6	200	60	300	20	1200	80	10	250	1.25
2	50.8	2.504	63.6	200	60	300	20	1200	80	12	300	1.87
2 1/2	63.5	3.004	76.3	200	60	300	20	1200	80	16	400	2.30
3	76.2	3.622	92	200	60	300	20	1200	80	20	500	3.23
4	101.6	4.717	119.8	200	60	300	20	1200	80	28	700	4.97
6	152.4	6.925	175.9	100	30	300	20	1200	80	48	1200	9.30
8	203.2	9.05	230	100	30	300	20	1200	80	64	1600	14.50

Authorized Distributor: GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service