

## ANTI- STATIC OIL DISCHARGE HOSE

200 PSI / 14 BAR

MADE IN ITALY



## TechnoFlex Oil Discharge Hose - 200 PSI / 14 BAR

A lightweight, flexible hose designed for oil discharge applications on trucks, docks, and barges where easy handling is essential, and vacuum resistance is not required. Also suited for oil field liquid mud transfers, it delivers reliable performance in demanding environments. Its durable construction ensures efficiency in industrial and marine operations.

- Temperature range:
  - -30°C to +80°C (-20°C to +180°F)
- Reinforcement:
  - o textile piles with static wire.
- Tube:
  - Black high grade of oil resistant (NBR).
- Cover:
  - o Abrasion, oil, weather & ozone resistant Neoprene (CR).
- Standard length:
- o 30m/60m
- **Safety Factor:** 
  - 0 4:1

ноѕ	HOSE I.D.		HOSE O.D.		WORKING PRESSURE		BURST PRESSUER	
in	mm	in	mm	psi	bar	psi	bar	Kg/m
1 ½	38.1	1.965	49.9	200	14	800	56	1.07
2	50.8	2.465	62.6	200	14	800	56	1.35
3	76.2	3.575	90.8	200	14	800	56	2.44
4	101.6	4.638	117.8	200	14	800	56	3.50
6	152.4	6.803	172.8	200	14	800	56	6.55
8	203.2	8.913	226.4	200	14	800	56	9.81

**Authorized Distributor:** GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service