

## **ANTI-STATIC** STEAM HOSE

**MADE IN ITALY** 

## TECHNOFLEX - ITALY ANTI-STATIC STEAM HOSE W. P. 250PSI/17 BAR



## TechnoFlex Steam Hose - 250 PSI / 17 BAR

A highly flexible, heat-resistant hose designed for steam applications in demanding industrial environments, including refineries, shipyards, chemical plants, steel mills, and foundries. Engineered to withstand high temperatures up to 210°C and a constant pressure of 250 PSI, it features uniform thickness for enhanced durability and reliability. Its robust construction ensures long-lasting performance, making it a dependable choice for heavy-duty industries requiring efficient and safe steam transfer.

- Temperature Range:
  - Service temperature upto +210°C (+410°F)
- Reinforcement:
  - o Double braid of high-tensile steel wire.
- Tube:
  - Heat resistant EPDM rubber compound.
- Cover:
  - Heat resistant EPDM rubber compound resistant to heat, ozone & a geing.
- Applicable STD:
  - IS 10655 TYPE III, BS 5342 TYPE 2, ISO 6134
- **Standard Length:** 
  - o 40m /60m
- **Safety Factor:** 
  - 0 10:1

HOSE I.D.		HOSE O.D.		WORKING PRESSURE		BURST PRESSUER		WEIGHT
mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
13	1/2 "	25	1"	17	247	170	2465	0,530
16	5/8 "	28	1-7/64 "	17	247	170	2465	0,600
19	3/4 "	32	1-1/4 "	17	247	170	2465	0,750
25	1 "	38	1-1/2 "	17	247	170	2465	0,950
32	1-1/4 "	46	1-12/16 "	17	247	170	2465	1,300
38	1-1/2 "	52	2-3/64 "	17	247	170	2465	1,580
51	2 "	68	2-11/16 "	17	247	170	2465	2,300
63.5	2-1 "	79.5	3-1/8 "	17	247	170	2465	3,300
76.2	3 "	93	3-21/32 "	17	247	170	2465	5,500
101.6	4"	124	4-7/8 "	17	247	170	2465	7,500

**Authorized Distributor:** GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service