



ANTI STATIC FUEL HOSE

MADE IN ITALY

- **TYPE**
Mandrel-built Hose
- **FINISHING**
Wrapped surface
- **APPLICATION**
20 BAR (300 PSI) light weight petroleum (50% aromatics) delivery hose not requiring robust construction.
- **TUBE**
Black color of NBR blend with static conducting.
- **COVER**
Black color of chloroprene blend it is resistant to ozone crack, abrasion and weather condition.
- **MARKING**
Using long length stripe.
- **TEMPERATURE**
- 40 C to + 100 C or (-40 F to + 212 F).
- **REINFORCEMENT**
Using multiple layers of high tensile tire cord, Using standard anti static wire.

Internal Diameter		Outside Diameter		Wall	Tolerance		Work Pressure		Service	Approx Weight		Hose Length	
mm	Inch	mm	Inch	Mm	+ mm	+ inch	BAR	PSI	Factor	Kg/M	Lbs/ft	meter	feet
13	½	24	0.94	5.50	0.79	0.031	20	300	1:3	0.528	0.354	30.5	100
19	¾	30	1.18	5.50	0.79	0.031	20	300	1:3	0.699	0.469	30.5	100
25	1	37	1.46	6.00	1.59	0.063	20	300	1:3	0.965	0.647	30.5	100
32	1 - ¼	46	1.81	7.00	1.59	0.063	20	300	1:3	1.417	0.949	30.5	100
38	1 - ½	52	2.05	7.00	1.59	0.063	20	300	1:3	1.635	1.095	30.5	100
51	2	65	2.56	7.00	1.59	0.063	20	300	1:3	2.107	1.412	30.5	100

Authorized Distributor:
GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service

E-mail: sales@geo-mac.com
www.geo-mac.com

Shop No. 0, Building 270, Road / Street 336
Block 312, MANAMA / ALGUFUL
Kingdom of Bahrain

Phone Number: +973 17769636