TECHNOFLEX ITALY



MULTIPURPOSE HOSE - 300 PSI

General Service Hose for a wide variety of Ar, Water and Nitrogen Applications, Specially designed for excellent sunlight and ozone resistance

TUBE: NBR - Oil resistant synthetic rubber

REINFORCEMENT: One or multiple layers of Textile reinforced subject-

ed to ID (1.1/4",1.1/2"and 2" double braid)

COVER: NBR/EPDM -rubber resistant to Ozone & Weather

TEMP RANGE: -40° C +100° C (-40° F +212° F)

APPLICATIONS: For Oil / Fuel / Water / Air / Nitrogen

Excellent Weather, Oil and Abrasion Resistance

ur · Available in Multiple Colours

	colour . Available ili multiple colours							
•		▶ ○◀		©				
DIAMETRO INTERNO Internal Diameter		DIAMETRO ESTERNO External Diameter		PRESSIONE ESERCIZIO Working Pressure		PRESSIONE SCOPPIO Burst Pressure		PESO NOMINALE Nominal Weight
mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
6	1/4″	13	1/2"	20	290	60	870	0,160
6	1/4"	14	9/16"	20	290	60	870	0,190
8	5/16"	16	5/8"	20	290	60	870	0,220
8	5/16"	17	43/64"	20	290	60	870	0,270
10	3/8"	18	23/32"	20	290	60	870	0,260
10	3/8"	19	3/4"	20	290	60	870	0,310
13	1/2"	22	7/8"	20	290	60	870	0,370
13	1/2"	23	29/32"	20	290	60	870	0,430
16	5/8"	25	1″	20	290	60	870	0,440
16	5/8"	26	1-1/32"	20	290	60	870	0,500
19	3/4"	29	1-9/64"	20	290	60	870	0,570
19	3/4"	30	1-3/16"	20	290	60	870	0,640
25	1″	36	1-27/64"	20	290	60	870	0,790
25	1″	37	1-29/64"	20	290	60	870	0,880

Via delle Acacie, 12 Z.E. D20 2805 GRIGNASCO (NO) ITAL'

GEOMAC